



SAFETY DATA SHEET

1. Identification

Product identifier Dip-it Whip-it Liquid Rope Whipping

Other means of identification

Product code 849-Red

Recommended use Sealant.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Star brite Inc.
Address 4041 SW 47th Avenue
Fort Lauderdale, FL 33314 US

Telephone General Information: (954) 587-6280

E-mail Not available.

Contact person Vincent Waclawek

Emergency phone number 24-Hour Emergency: CHEMTREC: (703) 527-3887
or (800) 424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 1

Health hazards Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Sensitization, skin Category 1
Reproductive toxicity Category 2
Specific target organ toxicity, repeated exposure Category 2
Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary statement

Prevention Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Contaminated work clothing must not be allowed out of the workplace. Avoid breathing mist/vapors/spray.

Response	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a poison center/doctor if you feel unwell. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Toluene	108-88-3	30 - 40
Methyl ethyl ketone	78-93-3	15 - 25
Acetone	67-64-1	1 - 5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. May cause allergic skin reaction. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Causes damage to organs (central nervous system, kidney, liver, respiratory system) through prolonged or repeated exposure. May cause drowsiness or dizziness.
Indication of immediate medical attention and special treatment needed	Treat symptomatically. Symptoms may be delayed.
General information	Get medical attention if symptoms occur. Wash contaminated clothing before re-use. Wash contaminated clothing before reuse. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media	Water. Water spray. Foam. Dry powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	Containers may explode when heated. Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Not available.
Fire-fighting equipment/instructions	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Specific methods	Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Eliminate all sources of ignition. Wear appropriate personal protective equipment (See Section 8).

Methods and materials for containment and cleaning up Eliminate sources of ignition. Take precautionary measures against static discharge. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.

Environmental precautions Avoid release to the environment.

7. Handling and storage

Precautions for safe handling Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin, and clothing. See Section 8 of the SDS for Personal Protective Equipment. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities Keep only in the original container in a cool, well-ventilated place. Do not handle or store near an open flame, heat or other sources of ignition. Store in a closed container away from incompatible materials. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m ³ 200 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m ³ 250 ppm
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m ³ 300 ppm
	TWA	590 mg/m ³ 200 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m ³ 150 ppm
	TWA	375 mg/m ³ 100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Explosion-proof general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other Wear chemical protective equipment that is specifically recommended by the manufacturer.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 1910.134. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Thermal hazards Not available.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practices. Always observe national occupational health and hygiene requirements including requirements for medical surveillance.

9. Physical and chemical properties

Appearance Red liquid.

Physical state Liquid.

Form Liquid.

Color Red.

Odor Solvent -like.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -139 °F (-95 °C)

Initial boiling point and boiling range Not available.

Flash point 45.0 °F (7.2 °C) Closed Cup

Evaporation rate Slower than ether

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	1800 - 2000 cP
Other information	
Density	0.96
Percent volatile	57.75 % By Weight
VOC (Weight %)	4.65 lb/gal 558 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. High temperatures. Contact with incompatible materials.
Incompatible materials	Amines. Ammonia. Caustics. Isocyanates. Strong acids. Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	Harmful by inhalation.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritant effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	20 ml/kg
Methyl ethyl ketone (CAS 78-93-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 8000 mg/kg
<i>Inhalation</i>		
LC50	Rat	11700 mg/l, 4 Hours

Components	Species	Test Results
Oral LD50	Rat	2300 - 3500 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not assigned.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
21.6 - 23.9 mg/l, 48 hours		4740 - 6330 mg/l, 96 hours
Methyl ethyl ketone (CAS 78-93-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)
4025 - 6440 mg/l, 48 hours		> 400 mg/l, 96 hours

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

Acetone (CAS 67-64-1)	-0.24
Methyl ethyl ketone (CAS 78-93-3)	0.29

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 °F
D035: Waste Methyl ethyl ketone

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)	U002
Methyl ethyl ketone (CAS 78-93-3)	U159
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products Dispose in accordance with applicable federal, state, and local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

UN number UN1993
UN proper shipping name Flammable liquids, n.o.s. (Acetone, Methyl ethyl ketone)
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Special precautions for user Not available.
Special provisions IB2, T7, TP1, TP8,TP28
Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242

IATA

UN number UN1993
UN proper shipping name Flammable liquid, n.o.s. (Acetone, Methyl ethyl ketone)
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards No.
ERG Code 3L
Special precautions for user Not available.

IMDG

UN number UN1993
UN proper shipping name FLAMMABLE LIQUID, N.O.S. (Acetone, Methyl ethyl ketone)
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant No.
EmS F-E, S-E*
Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

General information This product meets the limited quantities exception as follows:
DOT / IMDG: Limited quantities up to 1 liter.
Otherwise, the above descriptions apply.

15. Regulatory information

US federal regulations This product is hazardous according to OSHA 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED
Toluene (CAS 108-88-3)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene	108-88-3	30 - 40

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532
 Methyl ethyl ketone (CAS 78-93-3) 6714
 Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn
 Methyl ethyl ketone (CAS 78-93-3) 35 % weight/volumn
 Toluene (CAS 108-88-3) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532
 Methyl ethyl ketone (CAS 78-93-3) 6714
 Toluene (CAS 108-88-3) 594

US state regulations WARNING: This product contains chemicals known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
 Methyl ethyl ketone (CAS 78-93-3)
 Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
 Methyl ethyl ketone (CAS 78-93-3)
 Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
 Methyl ethyl ketone (CAS 78-93-3)
 Toluene (CAS 108-88-3)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
 Methyl ethyl ketone (CAS 78-93-3)
 Toluene (CAS 108-88-3)

US. California Proposition 65**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Toluene (CAS 108-88-3)

Canadian regulations

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS status

Controlled

WHMIS classification

B2 - Flammable/Combustible
 D1B - Immediate/Serious-TOXIC
 D2A - Other Toxic Effects-VERY TOXIC
 D2B - Other Toxic Effects-TOXIC

WHMIS labeling**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	
Europe	Inventory of Existing and New Chemical Substances (ENCS)	No
Japan	Existing Chemicals List (ECL)	Yes
Korea	New Zealand Inventory	Yes
New Zealand	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Philippines		Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).


A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 18-June-2014

Revision date -

Version # 01

NFPA Ratings

References

ACGIH
EPA: Acquire database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Star brite assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Star brite assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.