

Version: 3.0

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Date of issue: 04/14/2015

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture

Product Name: Sea Safe All Purpose Citrus Cleaner & Degreaser

Product Code: 89722

Intended Use of the Product

Cleaner

Name, Address, and Telephone of the Responsible Party

Company Star brite Inc.

4041 SW 47th Avenue Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency Number: US: (800) 424-9300; International: (703) 527-3887

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US) Eye Dam. 1 H318

Skin Sens. 1 H317

Full text of H-phrases: see section 16

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

Precautionary Statements (GHS-US): P261 - Avoid breathing vapors, mist, or spray.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - If on skin: Wash with plenty of water.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a poison center or doctor. P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P501 - Dispose of contents/container in accordance with local, regional, national,

territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 3 H402

H402 - Harmful to aquatic life.

P273 - Avoid release to the environment.

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

EN (English US) 1/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Tetrasodium EDTA	(CAS No) 64-02-8	1 - 5	Comb. Dust, H232
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation:dust,mist), H332
			Eye Dam. 1, H318
			Aquatic Acute 2, H401
Alcohols, C9-11, ethoxylated	(CAS No) 68439-46-3	1 - 5	Acute Tox. 4 (Oral), H302
·			Eye Dam. 1, H318
Dipropylene glycol monomethyl ether	(CAS No) 34590-94-8	0.1 – 1	Flam. Liq. 4, H227
Sodium xylene sulfonate	(CAS No) 1300-72-7	0.1 - 1	Eye Irrit. 2A, H319
Nitrilotriacetic acid trisodium salt†	(CAS No) 5064-31-3	< 0.1	Acute Tox. 4 (Oral), H302
		0.1 - 1	Eye Irrit. 2A, H319
			Carc. 2, H351
Sodium hydroxide	(CAS No) 1310-73-2	< 0.1	Met. Corr. 1, H290
·		0.1 - 1	Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Octylphenol ethoxylate	(CAS No) 9036-19-5	0.1 - 1	Acute Tox. 4 (Oral), H302
			Eye Dam. 1, H318
			Aquatic Acute 1, H400
			Aquatic Chronic 3, H412
D-Limonene	(CAS No) 5989-27-5	0.1 - 1	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			Skin Sens. 1, H317
			Asp. Tox. 1, H304
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area.

Skin Contact: Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage. May cause an allergic skin reaction.

Inhalation: May cause irritation to the respiratory tract.

Skin Contact: May cause an allergic skin reaction. May cause skin irritation.

Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva. Can cause blindness.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

^{*}More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

 $[\]dagger$ The carcinogen classification is applicable to the overall product only if this ingredient is >= 5% of the mixture. The Carc. 2 classification does not apply for this product.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry powder, alcohol-resistant foam, water in large amounts, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all eyes and skin contact and do not breathe vapor, mist, and spray.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Eliminate ignition sources. Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up.

Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Caustic products. Alkaline substances. Halogens.

Specific End Use(s)

Cleaner.

08/06/2015 EATT.B-VWCC EN (English US) 3/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Sodium lydroxide (1310-73-2) USA ACGH	the Mexican government			
USA NOSH				
USA NOSH				
US DIJH	USA OSHA			
Alberta OEL Ceiling (mg/m²) 2 mg/m²	USA NIOSH	NIOSH REL (ceiling) (mg/m³)		
Manitoba	USA IDLH			
New Brunswick OEL Ceiling (mg/m²) 2 mg/m²				
NewFoundland & Labrador OEL Ceiling (mg/m²) 2 mg/m³ 2 mg/m³ Novo Scotia OEL Ceiling (mg/m²) 2 mg/m³ 2 mg/m³ Nunavut OEL Ceiling (mg/m²)	British Columbia	OEL Ceiling (mg/m³)		
NewSouthand & Labrador OEL Ceiling (mg/m²) 2 mg/m³ 2 mg/m³ Nova Scotia OEL Ceiling (mg/m²) 2 mg/m³ 2 mg/m³ Northwest Territories OEL Ceiling (mg/m²) 2 mg/m³ 2 mg/m³ Ontario OEL Ceiling (mg/m²) 2 mg/m³ 2 mg/m³ Ontario OEL Ceiling (mg/m²) 2 mg/m³ 2 mg/m³ Ontario OEL Ceiling (mg/m²) 2 mg/m³ Outario OEL Ceiling (mg/m²) Outario OEL Ceiling (mg/m²) Outario	Manitoba	OEL Ceiling (mg/m³)		
Nora Scotia OEL Ceiling (mg/m²) 2 mg/m² 2 mg/m² Nunavut OEL Ceiling (mg/m²) 2 mg/m² 2 mg/m² 2 mg/m² Ontario OEL Ceiling (mg/m²) 2 mg/m² Ontario OEL Ceiling (mg/m²) 2 mg/m² Ontario OEL Ceiling (mg/m²) 2 mg/m² OEL Ceiling (mg/m²) 2 mg/m² OEL Ceiling (mg/m²)	New Brunswick	OEL Ceiling (mg/m³)	2 mg/m³	
Numavut	Newfoundland & Labrador	OEL Ceiling (mg/m³)		
Northwest Territories OEL Ceiling (mg/m²) 2 mg/m² Ontario OEL Ceiling (mg/m²) 2 mg/m² Prince Edward Island OEL Ceiling (mg/m²) 2 mg/m² Québec PLAFOND (mg/m²) 2 mg/m³ Saskatchewan OEL Ceiling (mg/m²) 2 mg/m³ Valkon OEL Ceiling (mg/m²) 2 mg/m³ Dipropylene glycol monomethyl ether (34590-94-8) USA ACGH ACGH TWA (ppm) 100 ppm USA ACGH ACGH STEL (ppm) 150 ppm USA ACGH ACGH Chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m²) 600 mg/m² USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA NOSH NIOSH REL (TWA) (mg/m²) 600 mg/m² USA NOSH NIOSH REL (TWA) (mg/m²) 600 mg/m² USA NOSH NIOSH REL (TWA) (mg/m²) 900 mg/m² USA NOSH NIOSH REL (TWA) (mg/m²) 900 mg/m² USA NOSH NIOSH REL (STEL) (mg/m²) 900 mg/m² USA DIDH US DIH (ppm) 150 ppm <tr< th=""><th>Nova Scotia</th><th>OEL Ceiling (mg/m³)</th><th>2 mg/m³</th></tr<>	Nova Scotia	OEL Ceiling (mg/m³)	2 mg/m ³	
Ontario OEL Ceiling (mg/m²) 2 mg/m² Prince Edward Island OEL Ceiling (mg/m²) 2 mg/m² Québec PLAFOND (mg/m²) 2 mg/m² Saskatchewan OEL Ceiling (mg/m²) 2 mg/m² Yukon OEL Ceiling (mg/m²) 2 mg/m² Dipropylene glycol monomethyl ether (34590-94-8) USA ACGH ACGH TWA (ppm) 100 ppm USA ACGH ACGH STEL (ppm) 150 ppm USA ACGH ACGH STEL (ppm) 150 ppm USA ACGH ACGH Chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m²) 600 mg/m² USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA OSHA Usinit value category (OSHA) prevent or reduce skin absorption USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (STEL) (ppm) 50 ppm USA DILI (ppm) 600 ppm 300 ppm Alberta	Nunavut	OEL Ceiling (mg/m³)	2 mg/m³	
Prince Edward Island OEL Ceiling (mg/m²) 2 mg/m³ Québec PLAFOND (mg/m²) 2 mg/m³ Saskatchewan OEL Ceiling (mg/m²) 2 mg/m³ Yukon OEL Ceiling (mg/m²) 2 mg/m³ Dipropylene glycol monomethyl ether (34590-94-8) USA ACGH ACGIH TWA (ppm) 100 ppm USA ACGH ACGIH STEL (ppm) 150 ppm USA ACGH ACGIH Hemical category Skn - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m³) 600 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA OSHA Jimit value category (OSHA) prevent or reduce skin absorption USA NOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NOSH NIOSH REL (TWA) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (ppm) 150 ppm USA NOSH NIOSH REL (STEL) (ppm)	Northwest Territories	OEL Ceiling (mg/m³)	2 mg/m³	
Québec PLAFOND (mg/m³) 2 mg/m³ Saskatchewan OEL Ceiling (mg/m³) 2 mg/m³ Yukon OEL Ceiling (mg/m²) 2 mg/m³ Dipropylene glycol monomethyl ether (34590-94-8) USA ACGIH ACGIH TWA (ppm) 100 ppm USA ACGIH ACGIH TWA (ppm) 150 ppm USA ACGIH ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m³) 600 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA OSHA Iimit value category (OSHA) prevent or reduce skin absorption USA NOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NOSH NIOSH REL (TWA) (ppm) 100 ppm USA NOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (ppm) 150 ppm <	Ontario	OEL Ceiling (mg/m³)	2 mg/m³	
Saskatchewan OEL Ceiling (mg/m³) 2 mg/m³ Yukon OEL Ceiling (mg/m²) 2 mg/m³ Dipropylene glycol monomettyl ether (34590-94-8) USA ACGH ACGIH TWA (ppm) 100 ppm USA ACGH ACGIH STEL (ppm) 150 ppm USA ACGH ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m³) 600 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA NOSH Imit value category (OSHA) prevent or reduce skin absorption USA NOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NOSH NIOSH REL (TWA) (ppm) 100 ppm USA NOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (ppm) 150 ppm USA NOSH OEL STEL (ppm) 150 ppm	Prince Edward Island	OEL Ceiling (mg/m³)	2 mg/m³	
Saskatchewan OEL Ceiling (mg/m³) 2 mg/m³ Yukon OEL Ceiling (mg/m²) 2 mg/m³ Dipropylene glycol monomettyl ether (34590-94-8) USA ACGH ACGIH TWA (ppm) 100 ppm USA ACGH ACGIH STEL (ppm) 150 ppm USA ACGH ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m³) 600 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA NOSH Imit value category (OSHA) prevent or reduce skin absorption USA NOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NOSH NIOSH REL (TWA) (ppm) 100 ppm USA NOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NOSH NIOSH REL (STEL) (ppm) 150 ppm USA NOSH OEL STEL (ppm) 150 ppm	Québec	PLAFOND (mg/m³)	2 mg/m³	
Yukon OEL Ceiling (mg/m²) 2 mg/m³ Dipropylene glycol monomettyl ether (34590-94-8) USA ACGIH ACGIH TWA (ppm) 100 ppm USA ACGIH ACGIH Chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m²) 600 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA OSHA OSHA PEL (TWA) (mg/m²) 600 mg/m³ USA OSHA Iimit value category (OSHA) prevent or reduce skin absorption USA NOSH NIOSH REL (TWA) (mg/m²) 600 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (STEL) (mg/m²) 900 mg/m³ USA NIOSH NIOSH REL (STEL) (mg/m²) 900 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm Alberta OEL STEL (mg/m²) 909 mg/m³ Alberta OEL TWA (mg/m²) 606 mg/m² Alberta OEL TWA (mg/m²) 606 mg/m² Alberta OEL TWA (ppm) 100 ppm British Columbia OEL TWA (ppm) 100 ppm	Saskatchewan	OEL Ceiling (mg/m³)	•	
Dipropylene glycol monomethyl ether (34590-94-8) USA ACGIH ACGIH TWA (ppm) 100 ppm USA ACGIH ACGIH STEL (ppm) 150 ppm USA ACGIH ACGIH stell (ppm) 150 ppm USA ACGIH ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m³) 600 mg/m³ USA OSHA Limit value category (OSHA) prevent or reduce skin absorption USA OSHA NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm Alberta OEL STEL (mg/m³) 909 mg/m³ Alberta OEL STEL (ppm) 150 ppm Alberta OEL STEL (ppm) 150 ppm British Columbia OEL STEL (ppm) 150 ppm British Columbia OEL STEL (ppm) 150 ppm Manitoba OEL STEL (mg/m³) 909 mg/m³	Yukon			
USA ACGIH ACGIH TWA (ppm) 100 ppm USA ACGIH ACGIH STEL (ppm) 150 ppm USA ACGIH ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m³) 600 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA OSHA Limit value category (OSHA) prevent or reduce skin absorption USA NIOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm USA DIH US DIH (ppm) 600 ppm Alberta OEL STEL (mg/m³) 909 mg/m³ Alberta OEL TWA (mg/m³) 606 mg/m² Alberta OEL TWA (ppm) 100 ppm British Columbia OEL TWA (ppm) 150 ppm British Columbia OEL TWA (ppm) 100 ppm New Brunswick OEL TWA (mg/m³) 606 mg/m³ <th>Dipropylene glycol monome</th> <th></th> <th></th>	Dipropylene glycol monome			
USA ACGIH USA ACGIH USA ACGIH USA ACGIH USA OSHA ACGIH chemical category USA OSHA USA NIOSH USA DIH USA DIH US DIH (ppm) USA DIH US DIL (ppm) USA DIH US DIL (ppm) USA DIH USA DIH US DIL (ppm) USA DIH USA DIL (ppm) USA DIL			100 ppm	
USA ACGIH ACGIH chemical category by the cutaneous route USA OSHA OSHA PEL (TWA) (mg/m²) 600 mg/m³ USA OSHA USA OSHA Limit value category (OSHA) USA NIOSH NIOSH REL (TWA) (mg/m²) BOD mg/m³ USA NIOSH NIOSH REL (TWA) (mg/m²) NIOSH REL (TWA) (ppm) DOD ppm USA NIOSH NIOSH REL (STEL) (mg/m³) NIOSH REL (STEL) (mg/m³) NIOSH REL (STEL) (ppm) NIOSH REL (STEL) (ppm) NIOSH REL (STEL) (ppm) DOD mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) NIOSH	USA ACGIH			
USA OSHA OSHA PEL (TWA) (mg/m³) 600 mg/m³ USA OSHA OSHA PEL (TWA) (ppm) 100 ppm USA OSHA Limit value category (OSHA) prevent or reduce skin absorption USA NIOSH Limit value category (OSHA) prevent or reduce skin absorption USA NIOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NIOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm Alberta OEL STEL (mg/m³) 909 mg/m³ Alberta OEL TWA (mg/m²) 100 ppm British Columbia OEL TWA (ppm) 100 ppm British Columbia OEL TWA (ppm) 100 ppm Manitoba OEL TWA (ppm) 100 ppm New Brunswick OEL STEL (ppm) 150 ppm		**	**	
USA OSHAOSHA PEL (TWA) (ppm)100 ppmUSA OSHALimit value category (OSHA)prevent or reduce skin absorptionUSA NIOSHNIOSH REL (TWA) (mg/m³)600 mg/m³USA NIOSHNIOSH REL (TWA) (ppm)100 ppmUSA NIOSHNIOSH REL (STEL) (mg/m²)900 mg/m³USA NIOSHNIOSH REL (STEL) (ppm)150 ppmUSA DIHUS DIH (ppm)600 ppmAlbertaOEL STEL (mg/m³)909 mg/m³AlbertaOEL STEL (ppm)150 ppmAbertaOEL TWA (mg/m³)606 mg/m³AlbertaOEL TWA (ppm)100 ppmBritish ColumbiaOEL STEL (ppm)150 ppmBritish ColumbiaOEL STEL (ppm)150 ppmManitobaOEL STEL (ppm)150 ppmManitobaOEL STEL (ppm)150 ppmNew BrunswickOEL STEL (mg/m³)909 mg/m³New BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNew BrunswickOEL TWA (ppm)100 ppmNew Gundland & LabradorOEL TWA (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)100 ppm				
USA OSHAOSHA PEL (TWA) (ppm)100 ppmUSA OSHALimit value category (OSHA)prevent or reduce skin absorptionUSA NIOSHNIOSH REL (TWA) (mg/m³)600 mg/m³USA NIOSHNIOSH REL (TWA) (ppm)100 ppmUSA NIOSHNIOSH REL (STEL) (mg/m²)900 mg/m³USA NIOSHNIOSH REL (STEL) (ppm)150 ppmUSA DIHUS DIH (ppm)600 ppmAlbertaOEL STEL (mg/m³)909 mg/m³AlbertaOEL STEL (ppm)150 ppmAbertaOEL TWA (mg/m³)606 mg/m³AlbertaOEL TWA (ppm)100 ppmBritish ColumbiaOEL STEL (ppm)150 ppmBritish ColumbiaOEL STEL (ppm)150 ppmManitobaOEL STEL (ppm)150 ppmManitobaOEL STEL (ppm)150 ppmNew BrunswickOEL STEL (mg/m³)909 mg/m³New BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNew BrunswickOEL TWA (ppm)100 ppmNew Gundland & LabradorOEL TWA (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)100 ppm	USA OSHA	OSHA PEL (TWA) (mg/m³)	1 0	
USA NIOSH NIOSH REL (TWA) (mg/m³) 600 mg/m³ USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm USA DIH US IDLH (ppm) 600 ppm Alberta OEL STEL (mg/m³) 909 mg/m³ Alberta OEL STEL (ppm) 150 ppm Alberta OEL TWA (mg/m³) 606 mg/m³ Alberta OEL TWA (ppm) 100 ppm British Columbia OEL STEL (ppm) 150 ppm British Columbia OEL TWA (ppm) 100 ppm Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL TWA (ppm) 100 ppm New Brunswick OEL STEL (mg/m³) 909 mg/m³ New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (mg/m³) 606 mg/m³ New Brunswick OEL TWA (ppm) 100 ppm New Brunswick OEL TWA (ppm) 100 ppm New Goundland & Labrador OEL TWA (ppm) 100 ppm <th>USA OSHA</th> <th></th> <th colspan="2"></th>	USA OSHA			
USA NIOSH NIOSH REL (TWA) (ppm) 100 ppm USA NIOSH NIOSH REL (STEL) (mg/m³) 900 mg/m³ USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm USA DIH US DLH (ppm) 600 ppm Alberta OEL STEL (mg/m³) 909 mg/m³ Alberta OEL TWA (mg/m³) 606 mg/m³ Alberta OEL TWA (ppm) 100 ppm British Columbia OEL STEL (ppm) 150 ppm British Columbia OEL TWA (ppm) 100 ppm Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL TWA (ppm) 100 ppm New Brunswick OEL STEL (mg/m³) 909 mg/m³ New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (mg/m³) 606 mg/m³ New Brunswick OEL TWA (ppm) 100 ppm New Brunswick OEL TWA (ppm) 100 ppm New Gundland & Labrador OEL STEL (ppm) 150 ppm Newfoundland & Labrador OEL TWA (ppm) 150 ppm	USA OSHA	Limit value category (OSHA)		
USA NIOSH NIOSH REL (STEL) (mg/m³) USA NIOSH NIOSH REL (STEL) (ppm) USA IDIH US IDIH (ppm) 600 ppm 600 ppm Alberta OEL STEL (mg/m³) 909 mg/m³ Alberta OEL STEL (ppm) 150 ppm Alberta OEL TWA (mg/m³) 606 mg/m³ Alberta OEL TWA (ppm) 100 ppm British Columbia OEL STEL (ppm) 150 ppm British Columbia OEL TWA (ppm) 100 ppm Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL STEL (ppm) 150 ppm New Brunswick OEL STEL (mg/m³) 909 mg/m³ New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (mg/m³) 606 mg/m³ New Brunswick OEL TWA (ppm) 100 ppm New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL STEL (ppm) 150 ppm	USA NIOSH	NIOSH REL (TWA) (mg/m³)		
USA NIOSH NIOSH REL (STEL) (ppm) 150 ppm USA IDIH US IDLH (ppm) 600 ppm Alberta OEL STEL (mg/m³) 909 mg/m³ Alberta OEL TWA (mg/m³) 606 mg/m³ Alberta OEL TWA (ppm) 150 ppm British Columbia OEL STEL (ppm) 150 ppm British Columbia OEL TWA (ppm) 100 ppm British Columbia OEL TWA (ppm) 100 ppm Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL STEL (ppm) 150 ppm New Brunswick OEL STEL (mg/m³) 909 mg/m³ New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (ppm) 100 ppm New Brunswick OEL TWA (ppm) 100 ppm New Brunswick OEL TWA (ppm) 150 ppm New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (ppm) 100 ppm	USA NIOSH	NIOSH REL (TWA) (ppm)		
USA IDIHUS IDIH (ppm)600 ppmAlbertaOEL STEL (mg/m³)909 mg/m³AlbertaOEL STEL (ppm)150 ppmAlbertaOEL TWA (mg/m³)606 mg/m³AlbertaOEL TWA (ppm)100 ppmBritish ColumbiaOEL STEL (ppm)150 ppmBritish ColumbiaOEL TWA (ppm)100 ppmManitobaOEL STEL (ppm)150 ppmManitobaOEL TWA (ppm)100 ppmNew BrunswickOEL STEL (mg/m³)909 mg/m³New BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNewfoundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)100 ppmNewfoundland & LabradorOEL TWA (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)100 ppm	USA NIOSH	NIOSH REL (STEL) (mg/m³)		
AlbertaOEL STEL (mg/m³)909 mg/m³AlbertaOEL STEL (ppm)150 ppmAlbertaOEL TWA (mg/m³)606 mg/m³AlbertaOEL TWA (ppm)100 ppmBritish ColumbiaOEL STEL (ppm)150 ppmBritish ColumbiaOEL TWA (ppm)100 ppmManitobaOEL STEL (ppm)150 ppmManitobaOEL TWA (ppm)100 ppmNew BrunswickOEL STEL (mg/m³)909 mg/m³New BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNewfoundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)100 ppm	USA NIOSH	NIOSH REL (STEL) (ppm)		
AlbertaOEL STEL (ppm)150 ppmAlbertaOEL TWA (mg/m³)606 mg/m³AlbertaOEL TWA (ppm)100 ppmBritish ColumbiaOEL STEL (ppm)150 ppmBritish ColumbiaOEL TWA (ppm)100 ppmManitobaOEL STEL (ppm)150 ppmManitobaOEL TWA (ppm)100 ppmNew BrunswickOEL STEL (mg/m³)909 mg/m³New BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNewfoundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)150 ppm	USA IDLH			
Alberta OEL TWA (mg/m³) 606 mg/m³ Alberta OEL TWA (ppm) 100 ppm British Columbia OEL STEL (ppm) 150 ppm British Columbia OEL STEL (ppm) 100 ppm Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL TWA (ppm) 100 ppm New Brunswick OEL STEL (mg/m³) 909 mg/m³ New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (mg/m³) 606 mg/m³ New Brunswick OEL TWA (ppm) 100 ppm New Brunswick OEL TWA (ppm) 100 ppm New Genswick OEL TWA (ppm) 100 ppm Newfoundland & Labrador OEL STEL (ppm) 150 ppm	Alberta	OEL STEL (mg/m³)	909 mg/m ³	
AlbertaOEL TWA (ppm)100 ppmBritish ColumbiaOEL STEL (ppm)150 ppmBritish ColumbiaOEL TWA (ppm)100 ppmManitobaOEL STEL (ppm)150 ppmNew BrunswickOEL STEL (mg/m³)100 ppmNew BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNew BrunswickOEL TWA (ppm)150 ppmNew foundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL STEL (ppm)150 ppm	Alberta	OEL STEL (ppm)		
British ColumbiaOEL STEL (ppm)150 ppmManitobaOEL STEL (ppm)150 ppmManitobaOEL TWA (ppm)100 ppmNew BrunswickOEL STEL (mg/m³)909 mg/m³New BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNew BrunswickOEL TWA (ppm)150 ppmNewfoundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)150 ppm				
British Columbia OELTWA (ppm) 100 ppm Manitoba OELSTEL (ppm) 150 ppm Manitoba OELSTEL (mg/m³) 100 ppm New Brunswick OELSTEL (mg/m³) 909 mg/m³ New Brunswick OELSTEL (ppm) 150 ppm New Brunswick OELTWA (mg/m³) 606 mg/m³ New Brunswick OELTWA (ppm) 100 ppm New Brunswick OELTWA (ppm) 150 ppm Newfoundland & Labrador OELSTEL (ppm) 150 ppm	Alberta	OEL TWA (ppm)	100 ppm	
Manitoba OEL STEL (ppm) 150 ppm Manitoba OEL TWA (ppm) 100 ppm New Brunswick OEL STEL (mg/m³) 909 mg/m³ New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (mg/m³) 606 mg/m³ New Brunswick OEL TWA (ppm) 100 ppm Newfoundland & Labrador OEL STEL (ppm) 150 ppm Newfoundland & Labrador OEL TWA (ppm) 100 ppm		OEL STEL (ppm)	150 ppm	
ManitobaOELTWA (ppm)100 ppmNew BrunswickOELSTEL (mg/m³)909 mg/m³New BrunswickOELSTEL (ppm)150 ppmNew BrunswickOELTWA (mg/m³)606 mg/m³New BrunswickOELTWA (ppm)100 ppmNewfoundland & LabradorOELSTEL (ppm)150 ppmNewfoundland & LabradorOELTWA (ppm)100 ppm	British Columbia	OEL TWA (ppm)	100 ppm	
New Brunswick OEL STEL (mg/m³) 909 mg/m³ New Brunswick OEL STEL (ppm) 150 ppm New Brunswick OEL TWA (mg/m³) 606 mg/m³ New Brunswick OEL TWA (ppm) 100 ppm Newfoundland & Labrador OEL STEL (ppm) 150 ppm Newfoundland & Labrador OEL TWA (ppm) 100 ppm		**	150 ppm	
New BrunswickOEL STEL (ppm)150 ppmNew BrunswickOEL TWA (mg/m³)606 mg/m³New BrunswickOEL TWA (ppm)100 ppmNewfoundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)100 ppm			**	
New Brunswick OELTWA (mg/m³) 606 mg/m³ New Brunswick OELTWA (ppm) 100 ppm Newfoundland & Labrador OELSTEL (ppm) 150 ppm Newfoundland & Labrador OELTWA (ppm) 100 ppm			909 mg/m ³	
New BrunswickOELTWA (ppm)100 ppmNewfoundland & IabradorOELSTEL (ppm)150 ppmNewfoundland & IabradorOELTWA (ppm)100 ppm		1 1		
Newfoundland & LabradorOEL STEL (ppm)150 ppmNewfoundland & LabradorOEL TWA (ppm)100 ppm	New Brunswick			
Newfoundland & Labrador OELTWA (ppm) 100 ppm	New Brunswick	OEL TWA (ppm)		
MI '	Newfoundland & Labrador	OEL STEL (ppm)	15 <mark>0 ppm</mark>	
Nova Scotia OEL STEL (ppm) 150 ppm		OELTWA (ppm)	100 ppm	
'I I I	Nova Scotia	OEL STEL (ppm)	150 ppm	

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nova Scotia	OELTWA (ppm)	100 ppm
Nunavut	OEL STEL (mg/m³)	909 mg/m³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m³)	606 mg/m ³
Nunavut	OELTWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m³)	909 mg/m ³
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OELTWA (mg/m³)	606 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	150 ppm
Ontario	OELTWA (ppm)	100 ppm
Prince Edward Island	OEL STEL (ppm)	150 ppm
Prince Edward Island	OELTWA (ppm)	100 ppm
Québec	VECD (mg/m³)	909 mg/m ³
Québec	VECD (ppm)	150 ppm
Québec	VEMP (mg/m³)	606 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OELTWA (ppm)	100 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties		
Physical State	: Liquid	
Appearance	: Clear Liquid	
Odor	: Characteristic	
Odor Threshold	: Not available	
pH	: 12	

рH **Evaporation Rate** Not available **Melting Point** 0 °C (32 °F) **Freezing Point** Not available **Boiling Point** 100 °C (212 °F) **Flash Point** Not available **Auto-ignition Temperature** Not available Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit Upper Flammable Limit** Not available

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Vapor Pressure Not available Relative Vapor Density at 20 °C Not available **Relative Density** Not available 1.0225 **Specific Gravity**

Solubility Soluble in water **Partition Coefficient: N-Octanol/Water** Not available Not available Viscosity

Explosion Data – Sensitivity to Mechanical Impact Not expected to present an explosion hazard due to mechanical impact. **Explosion Data - Sensitivity to Static Discharge** Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Sources of ignition. Incompatible materials. Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Caustic products. Alkaline substances. Halogens.

Hazardous Decomposition Products: Carbon oxides (CO, CO₃). Nitrogen oxides. Aldehydes. Ketones. Organic acids, Sulfur oxides.

Metal oxides. Sodium oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified ID50 and IC50 Data: Not available Skin Corrosion/Irritation: Not classified.

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 12

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. May cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva. Can cause blindness.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

Information on Toxicological Effects - Ingredient(s)

ID50 and IC50 Data:

LD50 Oral Rat

Tetrasodium EDTA (64-02-8)		
LD50 Oral Rat	1780 mg/kg	
ATE US (dust, mist)	1.50 mg/l/4h	
Nitrilotriacetic acid trisodium salt (5064-31-3)		
LD50 Oral Rat	1740 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
IC50 Inhalation Rat	> 5 mg/l/4h	
Dipropylene glycol monomethyl ether (34590-94-8)		

08/06/2015 IEATT.B-VWCC EN (English US) 6/13

5230 mg/kg

Sea Safe All Purpose Citrus Cleaner & DegreaserSafety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

ID50 Dermal Rabbit	9500 mg/kg		
Alcohols, C9-11, ethoxylated (68439-46-3)			
ID50 Oral Rat	D50 Oral Rat 1400 mg/kg		
ID50 Dermal Rat	> 2 g/kg		
D-Limonene (5989-27-5)			
ID50 Oral Rat	4400 mg/kg		
ID50 Dermal Rabbit > 5 g/kg			
ATE US (oral) 4,400.00 mg/kg body weight			
Octylphenol ethoxylate (9036-19-5)			
D50 Oral Rat 1700 mg/kg			
Sodium xylene sulfonate (1300-72-7)			
ID50 Oral Rat > 5000 mg/kg			
ID50 Dermal Rabbit	> 2000 mg/kg		
Nitrilotriacetic acid trisodium salt (5064-31-3)			
IARC Group	2B		
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.		
D-Limonene (5989-27-5)			
IARC Group	3		
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.		

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - **General:** Harmful to aquatic life.

Tetrasodium EDTA (64-02-8)			
IC50 Fish 1	486 (Exposure time: 96h - Species: Lepomis macrochirus)		
EC50 Daphnia 1	625 mg/l (Exposure time: 24 h - Species: Daphnia magna)		
ErC50 (algae)	3 mg/l (exposure time: 96 h - Species:Green Algae)		
Sodium hydroxide (1310-73-2)			
IC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])		
EC50 Daphnia 1	40 mg/l		
Nitrilotriacetic acid trisodium salt (5064-31-3)			
IC50 Fish 1	93 - 170 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])		
EC50 Daphnia 1	560 - 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
IC 50 Fish 2	175 - 225 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])		
Dipropylene glycol monomethyl ether (34590-94-8)			
IC50 Fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])		
EC50 Daphnia 1	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
D-Limonene (5989-27-5)			
IC50 Fish 1	0.619 - 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])		
IC 50 Fish 2	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)		
Octylphenol ethoxylate (9036-19-5)			
IC50 Fish 1	7.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])		
EC50 Daphnia 1	8.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [static])		
ErC50 (algae)	0.21 mg/l (Exposure time: 96 h - Species: Selenastrum Green Algae)		
Sodium xylene sulfonate (1300-72-7)			
EC50 Daphnia 1	> 1020 ml/l (Exposure time: 48 h - Species: Daphnia magna [Flow-through])		

Persistence and Degradability

Sea Safe All Purpose Citrus Cleaner & De	greaser
Persistence and Degradability	Not established.

08/06/2015 EATT.B-VWCC EN (English US) 7/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

1 1 1 (04700 04.0)

Dipropylene glycol monomethyl ether (34590-94-8)			
Persistence and Degradability	Readily biodegradable.		
Bioaccumulative Potential			
Sea Safe All Purpose Citrus Cleaner & Degreaser			
Bioaccumulative Potential	cumulative Potential Not established.		
Tetrasodium EDTA (64-02-8)			
Log Pow	5.01 (calculated)		
Dipropylene glycol monomethyl ether (34590-94-8)			
Log Pow	-0.064 (at 20 °C)		
Bioaccumulative Potential	Not expected to bioaccumulate.		

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport.

UN Proper Shipping Name Not regulated for transport.

Transport Hazard Class(es) Not regulated for transport.

Additional Information Not available

Marine Pollutant: No

Transport by sea Not regulated for transport.

Air transport Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Sea Safe All Purpose Citrus Cleaner & Degreaser		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
Tetrasodium EDTA (64-02-8)		
Listed on the United States TSCA (Toxic Substances Control Ac	t) inventory	
Sodium hydroxide (1310-73-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard		
Nitrilotriacetic acid trisodium salt (5064-31-3)		
Listed on the United States TSCA (Toxic Substances Control Ac	t) inventory	
Dipropylene glycol monomethyl ether (34590-94-8)		
Listed on the United States TSCA (Toxic Substances Control Ac	t) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test	
rule under TSCA.		
Alcohols, C9-11, ethoxylated (68439-46-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
D-Limonene (5989-27-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Octylphenol ethoxylate (9036-19-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Sodium xylene sulfonate (1300-72-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Tetrasodium EDTA (64-02-8)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sodium hydroxide (1310-73-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits Ceilings
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Ceilings
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits Ceilings
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits Ceilings
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- **U.S. Vermont Permissible Exposure Limits Ceilings**
- U.S. Washington Permissible Exposure Limits Ceilings
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Nitrilotriacetic acid trisodium salt (5064-31-3)

- U.S. Illinois Toxic Air Contaminant Carcinogens
- U.S. Illinois Toxic Air Contaminants

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- RTK U.S. Massachusetts Right To Know List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Dipropylene glycol monomethyl ether (34590-94-8)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- RTK U.S. Massachusetts Right To Know List
- U.S. Michigan Occupational Exposure Limits Skin Designations
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Skin Designations
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York Occupational Exposure Limits Skin Designations
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits Skin Designations
- U.S. Oregon Permissible Exposure Limits TWAs
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits Skin Designations
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Skin Designations
- **U.S. Vermont Permissible Exposure Limits STELs**
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits Skin Designations
- **U.S. Washington Permissible Exposure Limits STELs**
- U.S. Washington Permissible Exposure Limits TWAs

Alcohols, C9-11, ethoxylated (68439-46-3)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

D-Limonene (5989-27-5)

- U.S. Maine Chemicals of High Concern
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Chemicals of High Concern Persistent Bioaccumulative Toxins
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Octylphenol ethoxylate (9036-19-5)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sodium xylene sulfonate (1300-72-7)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Canadian Regulations

WHMIS Classification Class E - Corrosive Material

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects





Tetrasodium	EDTA ((64-02-8)
-------------	--------	-----------

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class E - Corrosive Material

Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1%

WHMIS Classification Class E - Corrosive Material

Nitrilotriacetic acid trisodium salt (5064-31-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class E - Corrosive Material

Dipropylene glycol monomethyl ether (34590-94-8)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1%

WHMIS Classification Class B Division 3 - Combustible Liquid

Alcohols, C9-11, ethoxylated (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects

D-Limonene (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1%

WHMIS Classification Class B Division 3 - Combustible Liquid

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Octylphenol ethoxylate (9036-19-5)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1%

WHMIS Classification Class E - Corrosive Material

Sodium xylene sulfonate (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 08/06/2015

08/06/2015 IEATT.B-VWCC EN (English US) 11/13

Sea Safe All Purpose Citrus Cleaner & Degreaser Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	cute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation: gas)	cute toxicity (inhalation: gas) Category 3
Acute Tox. 3 (Oral)	cute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation: dust,mist) A	cute toxicity (inhalation: dust,mist) Category 4
Acute Tox. 4 (Oral)	cute toxicity (oral) Category 4
Aquatic Acute 1 H	lazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2 H	lazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3 H	lazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1 H	lazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3 H	lazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	spiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Dam. 1 Se	erious eye damage/eye irritation Category 1
Eye Irrit. 2A Se	erious eye damage/eye irritation Category 2A
·	lammable liquids Category 3
	lammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A Sl	kin corrosion/irritation Category 1A
Skin Corr. 1B Sl	kin corrosion/irritation Category 1B
Skin Irrit. 2	kin corrosion/irritation Category 2
Skin Sens. 1 Sl	kin sensitization Category 1
H226 FI	lammable liquid and vapor
H227 Co	ombustible liquid
H232 M	May form combustible dust concentrations in air
H290 M	May be corrosive to metals
H301 To	oxic if swallowed
H302 H	Iarmful if swallowed
H304 M	May be fatal if swallowed and enters airways
H311 To	oxic in contact with skin
H314 Ca	auses severe skin burns and eye damage
H315 Ca	auses skin irritation
H317 M	May cause an allergic skin reaction
H318 Ca	auses serious eye damage
H319 Ca	auses serious eye irritation
	oxic if inhaled
Н332 Н	Iarmful if inhaled
H351 St	uspected of causing cancer
H400 V	very toxic to aquatic life
H401 To	oxic to aquatic life
H402 H	Iarmful to aquatic life
H410 V	ery toxic to aquatic life with long lasting effects
	Iarmful to aquatic life with long lasting effects

EN (English US) 12/13

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention was

given.

NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

08/06/2015 EATT.B-VWCC EN (English US) 13/13