

**1 IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY**

Product name : Star brite One Step Heavy Duty Clnr Wax-89632N, 89616DGP, 89632DGP,89632LM  
 Application : Boat maintenance. Polish.

Manufacturer : Star brite Distributing, Inc.  
 Address : 4041 S. W. 47 Avenue  
 Ft. Lauderdale, FL 33314  
 Telephone : +001- 954-587-6280

Distributor : Star brite Europe Inc.  
 Address : 30 rue F. Genin  
 F69005 Lyon, France  
 Telephone : +33- 472- 57 01 33  
 Fax : +33- 472- 57 04 93  
 Email : contact@starbrite-europe.com website: starbrite-europe.com

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:  
 : 001-703-527-3887 - CHEMTREC

**2 COMPOSITION / INFORMATION ON CONSTITUENTS**

Product description : Preparation.

Information on hazardous substances:

EC-name	Concentration (w/w) (%)	CAS-number	EC-number	Symbols	R-phrases
Kerosine (petroleum)	20 – 30	8008-20-6	232-366-4	Xn, N	10-38-51/53-65
Kaolin	5 – 10	92704-41-1	296-473-8	-	-
Naphthalene	< 1	91-20-3	202-049-5	Xn, N	22-40-50/53

Reference is made to chapter 16 for full text of each relevant R phrase. Occupational exposure limit(s), if relevant, are listed in section 8.

**3 HAZARD INFORMATION**

Classification : Flammable and dangerous to the environment.

Human health hazards : Low hazard for usual industrial or commercial handling. Contains petroleum distillates, may be harmful when ingested.

Physical/chemical hazards : Flammable.

Environmental hazards : Harmful to aquatic organisms, may cause longterm adverse effects in the aquatic environment. See also section 12.

Other information : Keep out of reach of children. If swallowed, seek medical advice immediately and show this container or label.

**4 FIRST AID MEASURES**

Effects and symptoms

- Inhalation : May cause headache, dizziness and a feeling of sickness.
- Skin contact : No specific effects and/or symptoms are known.
- Eye contact : May cause stinging of eyes and redness.
- Ingestion : May cause a feeling of sickness, vomiting and diarrhoea.

First aid measures

- Inhalation : Move victim into fresh air. Seek medical advice if victim feels unwell.
- Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up. Consult a doctor if irritation persists.
- Eye contact : Wash out with (lukewarm) water for at least 15 minutes. Remove contact lenses. Consult a doctor if irritation persists.



# MATERIAL SAFETY DATA SHEET

Ingestion : Do not induce vomiting. Give nothing to drink. Consult a doctor if victim feels unwell.

## 5 FIRE FIGHTING MEASURES

Extinguishing media  
 Suitable : CO2, foam, water fog or dry chemical.  
 Not suitable : Water jet  
 Special exposure hazards : None known  
 Hazardous thermal (de)composition products : Carbon monoxide may be evolved if incomplete combustion occurs.  
 Special protective equipment for fire-fighters : Use adequate respiratory equipment in case of insufficient ventilation.

## 6 ACCIDENTAL RELEASE MEASURES

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with nonslip soles. Keep away from sources of ignition. See also section 8.  
 Environmental precautions : Avoid release of product into sewers, surface and ground water causing pollution of the aquatic environment.  
 Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Dispose at an authorised waste collection point. Wash away remainder with plenty of water and soap.

## 7 HANDLING AND STORAGE

Handling : Handle in accordance with good occupational hygiene and safety practices in well ventilated areas.  
 Keep away from sources of ignition and direct sunlight. No smoking. Avoid contact with eyes and skin. Do not inhale vapours.  
 Storage : Keep frost-free, in a cool, dry and well-ventilated place (< 35 °C) separated from oxidizing substances. Protect from sunlight.  
 Recommended packaging : Keep only in the original container.  
 Use : Use only as directed.

## 8 EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with chemicals.  
 Hygienic measures : Do not eat, drink or smoke during use.  
 Occupational exposure limits : Occupational exposure limits have not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name		EC	UK		CEFIC-HSPA advice
Kaolin (respirable dust)	TGG 8 uur	-	2		575
	TGG 15 min.	-	-		
Kerosine (petroleum)	TGG 8 uur	-	-	-	
	TGG 15 min.	-	-	-	

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

Body protection : Use of specific protective industrial clothing is not required under normal conditions of use.  
 Respiratory protection : Take care of sufficient ventilation. Wear a gas filter type A (brown), class I or higher on e.g. a facemask in accordance with EN 140, in case of large scale exposure  
 Hand protection : Under normal conditions of use specific gloves are not required.  
 Eye protection : Wear appropriate safety glasses when there is danger of possible eye contact.

<b>9</b>	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
----------	---

Appearance : Viscous liquid  
 Colour : White  
 Odour : Hydrocarbons  
 pH : 9.3  
 Solubility in water : Insoluble  
                   in fat : Not known  
 Partition coefficient : Not known  
 (n-octanol/water)  
 Flash point : 58.9°C (PMcc)  
 Auto ignition temperature : Not applicable  
 Boiling point/ boiling range : Not known  
 Melting point/ melting range : ± 0°C  
 Explosive properties : Not known  
 Oxidizing properties : Not applicable  
 Decomposition temperature : Not applicable  
 Viscosity (40°C) : > 7 cSt  
 Vapour pressure (20°C) : Not known  
 Relative density (20°C) : ± 1 kg/l  
 Evaporation rate : Not known (n-butyl acetate = 1)

<b>10</b>	<b>STABILITY AND REACTIVITY</b>
-----------	---------------------------------

Stability : Stable under normal conditions.  
 Conditions to avoid : See section 7.  
 Materials to avoid : Keep away from oxidizing substances.  
 Hazardous decomposition products : None known.

<b>11</b>	<b>TOXICOLOGICAL INFORMATION</b>
-----------	----------------------------------

No toxicological research has been carried out on this product.

Inhalation : Stinging of respiratory airways possible when vapour concentrations exceed threshold limits.  
 Skin contact : Unlikely to cause irritation.  
 Eye contact : Slight irritation possible.  
 Ingestion : Ingestion may cause vomiting, nausea and diarrhoea. After ingestion, at vomiting, risk of aspiration in the lungs.

<b>12</b>	<b>ECOLOGICAL INFORMATION</b>
-----------	-------------------------------

No ecotoxicological research has been carried out on this product.

Ecotoxicity : No ecotoxicological information available. Harmful to aquatic organisms.  
 Mobility : Spilled product can penetrate into the ground and get into the ground water and surface water.  
 Persistence – degradability : Data on the biodegradation of this product are not available. May cause long term adverse effects in the aquatic environment.  
 Bio accumulative potential : No specific information known.

Ecotoxicological information:

Chemical name	Toxicity (mg/l)	Log P(ow)	BCF	Degradability
Kerosine (petroleum)	EC <sub>50</sub> : 1 - 10 (fish, estimated value)	3.6 – 7.6	-	< 10 days (half life time)
Naphthalene	LC <sub>50</sub> : < 1	3,3		

<b>13</b>	<b>DISPOSAL CONSIDERATIONS</b>
-----------	--------------------------------

Product residues : Dispose empty pack with regular household waste. Treat product residues and non-empty pack as hazardous waste. Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Comment : Attention is drawn to the possible existence of mandatory and regulatory communal, national or local requirements governing disposal of waste.

<b>14</b>	<b>TRANSPORT</b>
-----------	------------------

UN number : UN 1993  
 Transport name : FLAMMABLE LIQUID, N.O.S. (hydrocarbons)

Land (road / railway)  
 ADR/RID class : 3  
 Classification code : F1  
 Packaging group : III

Sea  
 IMDG class : 3  
 Packaging group : III  
 EmS (fire / spill) : F-E / S-E  
 Marine pollutant : No

Air  
 IATA class : 3



Information in this section pertains to shipments of the material in limited quantity (up to 5 liter) containers. Shipments in containers greater than 5 liters require flammable sticker. This information does not apply to IATA.

<b>15</b>	<b>REGULATORY INFORMATION</b>
-----------	-------------------------------

Community regulations : EC classification (67/548/EEC - 99/45/EC) and other regulations

Hazard symbols : None

R- and S-phrases : R10 Flammable.  
                           R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
                           S2 Keep out of reach of children.  
                           S46 If swallowed, seek medical advice immediately and show this container or label.

Other information : This product is exempted from classification as "Harmful: may cause lung damage if swallowed" on basis of point 3.2.3 of Annex VI of Directive 67/548/EC.

<b>16</b>	<b>OTHER INFORMATION</b>
-----------	--------------------------

The information in this safety data sheet is compiled in compliance with Directive 2001/58/EC dated 27 July 2001 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (\*).

Full text of R-phrases mentioned in section 2:



## MATERIAL SAFETY DATA SHEET

---

R10 Flammable.  
R38 Irritating to skin.  
R40 Limited evidence of a carcinogenic effect.  
R51/53 Toxic to aquatic organisms, may cause longterm adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.

---

### **History**

Date of first issue : 24-06-2005